

NE55 - NE75



NIRVANA

NIRVANAHP.COM

NE55 / NE75 HEAT PUMPS

EFFICIENT AND COMPACT



Energy efficient



Quiet



Compact size



Heat and cool





Developped
in North America



Enviromentally
friendly



Easy to use



Warranty – Canada
5 years – Parts & labor

MODEL NE SERIE		NE55	NE75
(80/80/80 – AHRI) ¹	BTU / COP	55 000 / 6.0	73 500 / 5.9
(80/63/80 – AHRI) ¹	BTU / COP	52 000 / 5.7	69 000 / 5.3
(50/63/80 – AHRI) ¹	BTU / COP	35 000 / 4.0	46 500 / 4.0
REFRIGERANT		R410A	R410A
MINIMUM / MAXIMUM BREAKER (A)		20 / 30	30
AMPS (A)		14	18.5
DECIBEL AT 10 METERS		48	50
VENTILATION		16"	22"
HEAT EXCHANGER		TWISTED TITANIUM DOUBLE COIL CANISTER	
DEFROST		ACTIVE (HOT GAS)	ACTIVE (HOT GAS)
CONTROL BOARD		DIGITAL	DIGITAL
COMPRESSOR TYPE		MITSUBISHI ROTARY	MITSUBISHI ROTARY
VOLTAGE		240V / 60HZ / 1 PHASE	240V / 60HZ / 1 PHASE
CABINET		ABS WITH METAL FRAME	ABS WITH METAL FRAME
WATER FLOW (GPM)		15 - 60	15 - 60
DIMENSIONS IN INCHES (W X L X H)		39.2 X 15.2 X 25.9	45.3 X 17.9 X 29.9
WEIGHT (LBS)		135	190
WATER CONNECTION		1.5" QUICK CONNECT FITTINGS (INCLUDED)	
POOL DIMENSIONS – ABOVE GROUND		UP TO 21'	UP TO 24'
POOL DIMENSIONS – INGROUND		UP TO 15' X 30'	UP TO 16' X 32'
POOL CAPACITY (LITERS)		UP TO 40 000 LITERS	UP TO 55 000 LITERS

ENERGY EFFICIENCY AT LOW TEMPERATURES IS THE MOST IMPORTANT THING TO CONSIDER

NIRVANA heat pumps, ranked AHRI #1 for low-temperature efficiency, offer the lowest operating costs in the industry. The coefficient of energy performance (COP) measures their ability to extract energy from the air and transfer it to the pool water, and a high COP guarantees lower heating costs. Certify your smart purchase with AHRI-validated performance at www.AHRINET.org.

¹Rated according to AHRI 1160: Ambient temperature (°F) / Relative humidity (%)
Water temperature (°F). With a water flow rate of 0.45 GPM per 1,000 BTU as per AHRI 80/63/80.