**NE55 - NE75** 



## NE55 / NE75 HEAT PUMPS EFFICIENT AND COMPACT



Energy efficient



Compact size



Quiet



Heat and cool



NIRVANA



Enviromentally friendly

.



Developped in North America

2 years warranty

MODEL NE SERIE		NE55	NE75
(80/80/80 – AHRI) <sup>1</sup>	BTU / COP	55 000 / 6.0	73 500 / 5.9
(80/63/80 – AHRI) <sup>1</sup>	BTU / COP	52 000 / 5.7	69 000 / 5.3
(50/63/80 – AHRI) <sup>1</sup>	BTU / COP	35 000 / 4.0	46 500 / 4.0
REFRIGERANT		R410A	
MINIMUM / MAXIMUM BREAKER (A)		20/30	30
AMPS (A)		14	18.5
DECIBEL AT 10 METERS		48	50
VENTILATION		16"	22"
HEAT EXCHANGER		TWISTED TITANIUM DOUBLE COIL CANISTER	
DEFROST		ACTIVE (HOT GAS)	
CONTROL BOARD		DIGITAL	
COMPRESSOR TYPE		MITSUBISHI ROTARY	
VOLTAGE		240V / 60HZ / 1PHASE	
CABINET		ABS WITH METAL FRAME	
WATER FLOW (GPM)		15 - 60	
DIMENSIONS IN INCHES (W X L X H)		39.2 X 15.2 X 25.9	45.3 X 17.9 X 29.9
WEIGHT (LBS)		135	190
WATER CONNECTION		1.5" QUICK CONNECT FITTINGS (INCLUDED)	
POOL DIMENSIONS - ABOVE GROUND		UP TO 21'	UP TO 24'
POOL DIMENSIONS - INGROUND		UP TO 15' X 30'	UP TO 16' X 32'
POOL CAPACITY (GALLONS)		UP TO 11 000 GALLONS	UP TO 15 000 GALLONS

<sup>1</sup>Rated and Certified in accordance with the AHRI 1160 Standard: Ambient Air (°F), Humidity (%) / Water Temperature (°F) at a water flow of 0.45gpm / 1000btu of capacity at the 80/63/80 btu rating. Pool Dimensions listed for reference only- Results may vary based on region, ambient air temperatures, and use of a solar blanket.